

ATTENTION:

Read before installation

- In cold weather, your bladder may be stiff and hard to work with. Two minutes with a hair dryer down in the bladder will alleviate this problem. Be sure not to leave the dryer right next to the wall of the bladder, as it may burn or scorch.
- Removal of the top ring is NOT necessary when installing the bladder into the hard tank. The ring has been attached with a sealer and has received 60 inch pounds of torque before it leaves the manufacturer. **DO NOT REMOVE THE TOP RING!** To install, simply heat, fold, and push the bladder through the front opening of the tank. Attach by lifting the pickup ring and aligning the pickup in the hard tank with that of the bladder. The bolts and washers are supplied and can be found in the component kit, which is inside your bladder upon arrival. Once attached, make sure the bladder is completely unfolded and forms to the inside of the hard tank as much as possible.
- If your bladder is equipped with a filter, the hose has already been attached to the filter; however, we do not install a hose clamp. If you wish to do that after market, please follow these instructions. Reach into the bladder through the top ring. Put your hand through the slit that is cut into the baffle, grab the filter and pull it out with the hose still attached. To reinstall, feed the hose through the anchor that is built in the back for the filter. and through the hole in the baffle. Then, seat the filter back into its' anchor and attach the hose to the bulkhead.
- **It is your responsibility to check the inside of the hard tank for any bolt ends or loose materials that may be abrasive to the bladder.**
- We have also included a list of correct and incorrect procedures. Please read before installation.

If you have any further questions about proper installation, please contact us toll free at 1-877-235-1388.