



In order to receive the best performance from your *APG Fuel Cell* we have compiled a list of correct and incorrect procedures.

CORRECT PROCEDURES

1. Read and Understand all product information before you begin.
2. Be sure to return your warranty card to APG upon receipt or warranty is void.
3. For Methanol use only!!!
4. Use a fuel filter between the fuel cell and fuel pump.
5. Allow for adequate ventilation.
6. Be sure fuel cell lid is properly grounded to chassis.
7. Always drain fuel cell for storage and protect with an approved rubber protectant. Store away from light and moisture. Do not use petroleum based products on or near fuel cells.
8. Always do a fit test on tank and mounting brackets before installing fuel cell.
9. For easy installation inside hard tank (especially in cold climates) soften bladder walls by warming interior with a blow-dryer, set on a warm setting.
10. Contact Alliance Performance Group, Inc.

INCORRECT PROCEDURES

1. Gasoline is never to be used in fuel cell.
2. Make no attempts to repair your fuel cell.
3. Never use unapproved additives.
4. Fuel cell is never to be pressurized or inflated.
5. Never modify tank while fuel cell is installed.
6. Mounting bolts should never be torqued in excess of the bolts specifications.

Alliance Performance Group, Inc.
65 Columbia 300, Magnolia, AR 71753
Phone (870) 235-1300 Toll Free 877-235-1388 Fax (870)235-1301
Web address www.winapg.com
Email us at info@winapg.com